

Input data

System of measurement		Metric
Input type		Gear motor
Input speed	[rpm]	1400
Output speed	[rpm]	47.23
Ratio (i=)		29.64
Frequency	[Hz]	50
Input options		IEC
Requested input power	[kW]	3
Service factor		1.1
Rated Power P1	[kW]	3.35

Output data

Gear unit	M RD 42 B3 H1 29.64 100 B14 AU 35x70 MT 3 kW 100 B4 B14 X3
------------------	---

Type		RD - Helical gearboxes
Input type		M
Size		42
Ratio (i=)		29.64
Input flange		B14
Mounting position		H1
Input speed	[rpm]	1400
Output speed	[rpm]	47.23
Rated output torque	[Nm]	582.3
Service Factor		1.1
Efficiency		0.96
Inertia moment	[kgm ²]	0.000761

Gear unit configuration

Fixing		Feet
Output shaft		AU 35x70

Output radial and axial loads


Output radial load	[N]	6100
Output axial load	[N]	1220

Electric motor

Size		100 B4
Poles		4
Power	[kW]	3


Electric motor configuration

Motor flange		B14
Terminal box position		X3



M RD 42 B3 H1 29.64 100 B14 AU 35x70 MT 3 kW 100 B4 B14 X3

Mounting positions



Lubricant type: Long life synthetic oil ISO VG320

Direction of rotation



Weight

Gear unit [kg]	20
Electric motor [kg]	21

M RD 42 B3 H1 29.64 100 B14 AU 35x70 MT 3 kW 100 B4 B14 X3