

Input data

System of measurement		Metric
Input type		Gear motor
Input speed	[rpm]	1400
Output speed	[rpm]	23.37
Ratio (i=)		59.9
Frequency	[Hz]	50
Input options		IEC
Requested input power	[kW]	3
Service factor		1.1
Rated Power P1	[kW]	3.35

Output data

Gear unit **M RD 53 B3 H1 59.9 100 B5 AU 50x100 MT 3 kW 100 B4 B5 X3**

Type		RD - Helical gearboxes
Input type		M
Size		53
Ratio (i=)		59.9
Input flange		B5
Mounting position		H1
Input speed	[rpm]	1400
Output speed	[rpm]	23.37
Rated output torque	[Nm]	1152.26
Service Factor		1.1
Efficiency		0.94
Inertia moment	[kgm ²]	0.001439

Gear unit configuration

Fixing		Feet
Output shaft		AU 50x100

Output radial and axial loads


Output radial load	[N]	7800
Output axial load	[N]	1560

Electric motor

Size		100 B4
Poles		4
Power	[kW]	3


Electric motor configuration

Motor flange		B5
Terminal box position		X3




M RD 53 B3 H1 59.9 100 B5 AU 50x100 MT 3 kW 100 B4 B5 X3

Mounting positions



Lubricant type: Long life synthetic oil ISO VG320

Direction of rotation



Weight

Gear unit [kg]	52
Electric motor [kg]	21